

Space Micro Kit Encoder

Features

- » 1.5 Inch Diameter Kit (Frameless) Encoder
- » True Absolute 24-Bit Position Output
- » Accurate to <math><30</math> arcseconds RMS
- » In-Situ Auto-Calibration
- » Health and Status Diagnostic Reporting
- » Radiation tolerant to 50 krad(Si)

Applications

- » Commercial Space Applications
- » Low Earth Orbit
- » CubeSats
- » Miniature DC Motor
- » Robotics



Description

The Micro Kit Encoder, or MKE, is Quantic BEI's smallest flight-worthy optical encoder. This true-absolute optical encoder delivers high performance rotary sensing in a package well suited for CubeSats & small satellites. The code disk hub is customizable to fit small shafts <math><5</math> mm [3/16"], such as common DC motors. The electronic components are qualified to Level 1 or Level 2 per GSFC EEE-INST-002 and suited for all Earth-orbital applications.

Like other encoders in the nanoSeries family, the MKE employs a long-life LED light source to illuminate our high-accuracy code disk. The code patterns constitute radiometric tiers of advancing frequencies to create the high-resolution 24-bit contiguous angular position, all while maintaining positional stability over temperature and time.

	Specification	Units	Min	Max	
Performance	Full Revolution Accuracy	arcsec RMS	-	30	
	Resolution - Quanta	Bits	24	-	
	Resolution - ENOB	Bits	18	-	
	Interrogation Rate	Hz	100	1000	
	Data Relevancy	μS	43	48	
	Speed (operating)	RPM	0	1000	
	Reliability, MIL-HDBK-217	FIT, Failures/Billion Hours	114	-	
	Direction of Increasing Count	-	CCW		
Electrical	Input Voltage	VDC	4.3	5.5	
	Input Current	mA	-	50 [BOL] 90 [EOL] ¹	
	ESD Sensitivity	V, HBM	8000	-	
Environmental	Vibration, MIL-STD-202 Method 214, Condition I, Profile H	grms	-	29.28	
	Shock Response Spectrum	g's	-	Frequency	g's
				30	110
				1000	1500
	10000	1500			
	Operating Temperature	°C	-40	+70	
	Storage Temperature	°C	-55	+90	
	Low-Outgassing Design	-	-	1.0% TML 0.1% CVCM	
Total Ionizing Dose	krad	-	50		
Displacement Damage	n/cm ² [1 Mev]	-	> 2.4E11		

1. End of Life (EOL) maximum current based upon worst case analysis calculations. Consult factory.

Connector Pinout

The standard nanoSeries® Micro Kit Encoder output connector is a 9-socket Micro-D Connector (M83513/04-A_N type) with the following pinout:

Pin	MNEMONIC	I/O	Description
1	+POS	Out	Position data output
6	-POS	Out	Position data output
3	+CMD	IN	Command word input
8	-CMD	IN	Command word input
2	+CLK	IN	Synchronous clock input
7	-CLK	IN	Synchronous clock input
4	+5 VDC	—	Supply Voltage
9	5V RTN	—	Supply Voltage return
5	CHAS	—	Chassis (case) ground

I/O: LVDS



Output Protocol




Figure 1.
Electrical Interface
Timing Diagram (System)
Timing Values Per Table 1)



Table 1.
Electrical Interface Timing Values (See 190-0323-03 For Details)

Parameter	Symbol	Min	Typical	Max	Units
Encoder Data Relevancy*	T_{REL}	43	45.5	48	μ S
Encoder Interrogation Period	T_{INT}	1000	—	—	μ S
Clock Frequency		0.05	2	2.5	MHz


*Although data is sampled within 45 μ S (typ) of the CMD pulses, it is not shifted out until the next cycle

Readhead & Code Disk In Installed State

[Right-exit option, shown with front cover removed]



RIGHT-EXIT OPTION



LEFT-EXIT OPTION




Notes:


1. See outline drawing 190-0343-01 for complete dimensional specifications and mounting interface recommendations.
2. Unbracketed dimensions are inches and bracketed [x.Xx] dimensions are millimeters.
3. Quantic BEI can provide mounting plates to adapt stator interface to any existing hole pattern. Consult the factory for details.
4. Readhead mass: $50.3 + 1.35(L)$ grams max, L = cable length
Disk hub mass: 10.8 Grams max

Installation Sequence


1. Mount Hardware




2. Fully Insert Shim




3. Raise Disk to Shim



4. Remove Shim



5 Install Front Cover



Ordering Information

